Homax®

Wall Texture

Textura para pared

PRO GRADE

ORANGE PEEL

Cáscara de naranja



HOPPER GUN CONTROL™

Pressure & Spray Tip Adjustment

Delivers an Invisible Repair
No Prime, Lower Odor Formula
Dries in 5 Minutes

Ajuste en la Punta de Presión y Pulverización
Brinda una Reparación Invisible
Fórmula con menos Olor, Sin Imprimar
Se seca en 5 Minutos

DANGER! FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
Read other cautions on side/back panel before using.

¡PELIGRO! LÍQUIDO Y VAPOR INFLAMABLES. [illegible] EN LOS OJOS, LA PIEL Y LAS VÍAS RESPIRATORIAS. [illegible]

NET WT 25 OZ (709 g)

OIL BASED BASE DE ACEITE

Homax® Pro Grade Wall Texture with Dual Control™ technology is the latest innovation in aerosol textures. This professional tool features adjustment of both pressure and pattern – similar to that of a gun and hopper. The oil-based Pro Formula provides the same ultra-fast dry results as the original, but now with an advanced lower odor and no prime formulation. This time-saving tool provides portable and convenient delivery of a full range of texture patterns to achieve an invisible repair.

Watch a How-to Video at homaxproducts.com or scan this code to watch now!

Ver el Video Instructivo en homaxproducts.com o capture con su Smartphone para verlo ahora.

READ AND FOLLOW ALL WARNINGS AND PRECAUTIONS. PROTECT SURROUNDING AREA FROM OVERSPRAY. DO NOT SPRAY ON CLOTHING, FURNITURE OR CARPET.

DIRECTIONS FOR USE: MAKE NECESSARY WALL REPAIRS BEFORE APPLYING. SPOT PRIME REPAIR AREA BEFORE TEXTURE APPLICATION TO ENSURE BEST RESULTS. Priming after texture application is no longer needed. Always practice spraying on cardboard or scrap drywall to determine preferred pattern.

1. SHAKE CAN upside-down vigorously for one full minute before using and continuously during use.
2. REMOVE safety tab from top of trigger. REMOVE red clip from below pressure toggle. RETAIN red clip and reattach for storage.
3. ADJUST PATTERN: POINTING AWAY FROM FACE, TURN YELLOW SPRAY TIP TO DESIRED PATTERN: *CLOCKWISE for FINE, COUNTER CLOCKWISE for HEAVY*
4. ADJUST PRESSURE*: MOVE YELLOW TOGGLE: *RIGHT for HIGH, LEFT for LOW*
   *As contents and pressure in can decreases, adjust pressure and pattern to maintain a consistent texture appearance.
5. SPRAY at a distance of 18"-24" from wall using a circular (not sweeping) motion. Note: Depending upon PRESSURE & PATTERN settings, distance may vary. Sprays best between 65-80°F. Apply in a uniform pattern, covering only 80% of surface. Shake can occasionally throughout use.
   DRY TIME: Allow to dry 5-30 minutes before painting. Heavier textures may require longer dry time, dependent upon temperature and humidity.
   CLEAN-UP: Acetone, lacquer thinner or isopropyl alcohol.
6. AFTER USE/TO STORE: Clear nozzle by turning can upside down, move toggle to high pressure and spray until texture is cleared. Reattach red clip under pressure toggle for storage.
7. PAINT with 2 coats or more for complete hide and to match gloss (dependent upon color and paint manufacturer's instructions).



DANGER! Contains Nepheline Syenite, Diacetone Alcohol, Ethanol, Wollastonite, Titanium Dioxide and Propane/Isobutane blend (propellant). **FLAMMABLE.** Vapors may cause flash fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. May cause dizziness, headache or nausea. Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles and gloves. An appropriate and properly fitted NIOSH approved respirator may provide extra protection, but should only be used in accordance with manufacturer's directions for respirator use. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **CONTENTS UNDER PRESSURE.** Do not puncture or incinerate (burn) container. Do not expose to heat or store at temperatures above 120°F. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. **FIRST AID:** If swallowed, do not induce vomiting. Get medical attention immediately. For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention. **KEEP OUT OF REACH OF CHILDREN. WARNING:** This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LEA Y RESPETE TODAS LAS ADVERTENCIAS Y PRECAUCIONES. [illegible]

INSTRUCCIONES DE EMPLEO: HACER TODAS LAS REPARACIONES EN LAS PAREDES QUE SEAN NECESARIAS ANTES DE APLICAR EL PRODUCTO. [illegible] Siempre practique pulverizar sobre cartón o sobre un trozo de panel de yeso para determinar el modelo que prefiera.

1. [illegible]
2. RETIRAR la lengüeta de seguridad de la parte superior del gatillo. [illegible]
3. AJUSTAR EL MODELO [illegible]
4. AJUSTAR LA PRESIÓN [illegible]
5. PULVERIZAR a una distancia de 46 a 61 cm (18" a 24") de la pared [illegible]
   TIEMPO DE SECADO: [illegible]
   LIMPIEZA: Acetona, diluyente para lacas o alcohol isopropílico.
6. DESPUÉS DE USAR/PARA ALMACENAR [illegible]
7. DAR 2 capas de pintura o más [illegible]

¡PELIGRO! Los vapores pueden provocar [illegible]

Flat Paint Product VOC < 80% PMWR <1.20 [illegible]
Patents Pending.

HOMAX® A Premier Brand of THE [illegible]
Bellingham WA 98227
www.homaxproducts.com
800-729-9029

MADE IN USA

0 41072 04555 1